



Suede is an embossed, commercial grade PVC wallcovering with a poly cotton fabric backing. The suede embossing is similar to suede fabric with its nap and texture.

Wallcovering: Suede (Commercial Grade)



Overview	Suede is an embossed, commercial grade PVC wallcovering with a poly cotton fabric backing. The suede embossing is similar to suede fabric with its nap and texture.
Product Specifications	<ul style="list-style-type: none">• bleux product code is 'WCS'• Printed with UV inks• Designed for indoor use only• Heavy duty commercial grade for long-term applications• Mould, mildew and fungal resistant• Fire retardant• Optimised white point for superior imaging
For Specification Notes	<p>Finish: wallcovering (suede) Design: tbc (@bleux) Colourway: tbc Code: WCS-XXX-XXX Notes: Samples to be provided for sign off prior to ordering. To be installed by bleux or qualified installer. Design (based on site measurements) to be approved prior to manufacture. Lead time is 3 weeks from sign off of final shop drawings. No equivalent product will be considered. Contact: (02) 93806544 or quotes@bleux.com.au</p>
Warranty	7 year warranty (indoor use) against defects such as peeling, glue failure, bubbling, cracking, delaminating and fading when it is properly installed onto interior surfaces. Correct surface preparation is the responsibility of the party purchasing the wallcovering. This warranty only covers film installed by bleux.
Environmental	<ul style="list-style-type: none">• Cadmium and lead-free formulation• Made with Low VOC vinyl. No VOCs in wallcovering adhesive
Fire Rating	AS/NZS 3837-1998 Group 2
Considerations	<ul style="list-style-type: none">• The light texture works well to reduce glare from direct light• Most suited to gyprock walls. Due to the splice cut installation method it is not suitable for concrete rendered walls• Fabric backing provides easy installation

- Wall Preparation Introduction
- Correct surface preparation is the responsibility of the party purchasing the wallcovering
 - The finish of a surface prior to installation is essential to achieve the best possible results
 - If the wall preparation is not followed, bleux reserves the right to refuse install as it could lead to defects
-

- Wall Surface Preparation
- Suede can be applied to almost any properly prepared wall surface in sound condition
 - Holes and joins should be filled and sanded. Do not sand the raw paper faced board
 - Surface must be completely clean, smooth, dry and free of any dust particles, mildew, grease, stains and dust particles. Dirt and grime should be removed with a commercial detergent solution and water. If the surface has grease, oil or wax, it must be cleaned using a mild solvent wipe
 - Dust can create a textured surface underneath the suede wallcovering and affect adhesion. A dust-free environment is therefore required for the installation of suede to ensure maximum adhesion and the best quality finish
 - Old wallcoverings must be removed and sanding should dull enamel surfaces
 - All surfaces must be properly prepared using a professional latex based primer, such as Roman's R-35, or a white acrylic based, low sheen paint primer such as Dulux '1 Step Precoat'. Oil based products should be avoided
 - Adhesive and wallcovering must be room temperature for at least 24 hours prior to and during the installation
 - We recommend that all existing hardware including kickboards and face plates etc, are removed prior to installation. All hardware should be removed prior to bleux installers arriving on site, or alternatively new hardware should not be installed until after the installation is completed. If hardware is not removed and install needs to be rescheduled, rescheduling fees of up to \$800 can apply
-

- Prepping a Surface Prior to Installation
- bleux recommends PRO-880 Ultra® Clear Strippable Wallcovering Adhesive for application of suede wallcovering

Prepping a Surface Prior to Installation (continued)

- PRO-880 is a premium clear adhesive with excellent wet-tack, extended open-time and ease of clean up. It promotes strippability of fabric-backed wallcoverings over new bare drywall
- PRO-880 applies easily with a roller or pasting machine
- Spreads and flows easily

Installation

This product must be installed by experienced signage professionals. bleux can arrange for installation and site measures in all capital cities if required. It is the responsibility of the designer, contractor or builder to provide full site details and elevations indicating the locations of the specified bleux product. bleux will conduct a final site inspection if it is contracted to do so.

Supply and Install

It is bleux's preference to supply and install. Prices cover a non-staged install taking place within business hours from Monday to Friday. Anything outside of business hours will be quoted accordingly, available upon request. Wall preparation must be adhered to 72 hours prior to install.

Supply Only

Installers must follow the bleux site check form (available upon request) to ensure site check is conducted properly. If bleux products are being installed by an installer nominated by the client, bleux does not take responsibility for final installed product.

Care and Maintenance

- Ordinary dirt and smudges can be removed with mild soap and warm water. Clean from bottom of wall upward. Rinse thoroughly with clean water from the top down using a sponge
- Use a soft brush, rag or sponge. Never use a hard bristle brush
- Do not use solvents, alcohol, pine oil, ammonia or cleaners that contain these kinds of products as they can remove the digital print and damage the textured surface
- Do not use steel wool or powdered abrasive because they can damage the image and textured surface
- Embossed wallcoverings need extra attention to remove suds or loosened dirt that may lodge in the embossing. Dry wallcovering with a soft lint free cloth or towel

Wallcovering: Suede (Commercial Grade)



Care and Maintenance
(continued)

- For more difficult stains that are only surface deep, the use of a stronger detergent is recommended. Always test an inconspicuous area with the stronger detergent to be sure that the surface and ink are not damaged

More Details

Contact bleux at info@bleux.com.au or call 02 9380 6544

e&oe 27.9.19